

SOLIS

S26
SHUTTLE

9+9

SERIES



RELIABLE MECHANICAL
TRACTOR

POWER PACKED
ENGINE

TWIN PROJECTOR
HEADLAMPS

AGRI, IND & TURF
TYRE OPTION

REINFORCED SAFETY
FEATURES



MITSUBISHI
MOTORS



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

WWW.SOLISBELGIUM.BE

info@solisbelgium.be

| FEATURES | S 26 9+9 |
|-----------------------------|------------------------------------|
| Model Description | SOLIS-26 |
| ENGINE | |
| Engine Type | Mitsubishi 3-Cylinder Diesel Motor |
| HP Category | 26 |
| No. of Cylinders | 3 |
| Aspiration | Natural |
| Cubic Capacity (cc) | 1319 |
| Rated RPM | 2500 |
| Air cleaner | Dry with clogging sensor |
| Cold Start | Standard |
| Max Torque (nm) | 76.3 |
| Exhaust | Underhood Downdraft Silencer |
| TRANSMISSION | |
| Drive | 4WD (all-wheel switchable) |
| Clutch | Single Clutch |
| Gearbox | 9F+9R |
| Front Axle | 4WD |
| Transmission | Constant mesh with Synchro shuttle |
| SPEED (FORWARD) | |
| Maximum Speed (Km/Hr) | 21.46 @2760 fly up |
| Minimum Speed (Km/Hr) | 1.14@rated |
| BRAKES | |
| Brakes | Oil Immersed Brakes |
| Type of actuation | Mechanical |
| Parking Brake | Independent |
| DIFFERENTIAL LOCK | |
| Differential lock | Yes, Foot Operated |
| PTO | |
| PTO (rpm) | 540/540E |
| PTO (actuation) | Mechanical |
| STEERING | |
| Steering | Power |
| ELECTRICAL | |
| Battery | 12V, 65Ah |
| Type of Actuation | 12V, 42Amp |
| Trailer socket | Standard 7-pin |
| HYDRAULICS | |
| 3 point linkage | KAT 1-N |
| Stay Bars | Anchor Chain |
| Lifting Capacity | 600Kg |
| Auxiliary hydraulic circuit | 1DA |
| Lift rods | Standard |

| FEATURES | S 26 9+9 | | |
|--------------------------------------|-----------------------------------|---------------------------------------|-----------------------------------|
| SAFETY SWITCH | | | |
| Clutch Safety Switch | Standard | | |
| PTO Safety Switch | Standard | | |
| Neutral Safety Switch | Standard | | |
| CAPACITY (LTRS)(+/-5%) | | | |
| Fuel tank (Lit) | 20 | | |
| TURNING RADIUS | | | |
| Without Brakes (m) | 3.02 (RHS), 3.15 (LHS) | | |
| TYRE | | | |
| Front | 6.00-12 | | |
| Rear | 8.30-20 | | |
| DIMENSION & WEIGHT(+/-5%) | | | |
| Weight(kg) | 1250 | | |
| Wheel Base (mm) | 1570 | | |
| Total Length (mm) | 2895 | | |
| Total Width (mm) | 1215 (max)-1050 (min) | | |
| Height (mm) Up to ROPS | 2325 | | |
| Min Ground Clearance (mm) | 240 | | |
| Front Track (mm) | 885 | | |
| Rear Track (mm) | 960 | | |
| OTHERS | | | |
| Fuel Indicator gauge | Standard | | |
| Front Toe Hook | Standard | | |
| OPTIONAL FEATURES | | | |
| Tyres | | | |
| Agricultural Tyres (radial) | Turf Tyres | Industrial Tyres | Galaxy Pro Tyres |
| Front 6.5/80-12 Rear 280/70 R18 | Front 25x8,50-14 Rear 13.60-16 | Front 23x8.50-12 Rear 33x15.5-16.5 | Front 280/70R16 Rear 280/70r16 |

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.



ACCOLADES AND CREDENTIALS



AMONG TOP 6 TRACTOR MANUFACTURERS GLOBALLY*



AMONG TOP 3 TRACTOR COMPANIES IN INDIA



EMINENT PRESENCE IN 100+ COUNTRIES



WORKFORCE OF 5,000+ DEDICATED EMPLOYEES WITH 300+ ENGINEERS IN R&D



JOINT VENTURE WITH YANMAR (JAPAN)



PRODUCTION CAPACITY OF 300,000 TRACTORS PER YEAR

DURANT

WWW.SOLISBELGIUM.BE