







LIFTING CAPACITY
750 KG



MECHANICAL TRANSMISSION FOR SPEED PRECISION



HI-LOW SPEEDS LEVER



SLIDING MESH TRANSMISSION WITH 6+2 SPEED



SIDE SHIFT GEAR LEVER FOR COMFORT



3 CYLINDER DIESEL ENGINE



HIGH BACK UP ORQUE



526



LOW MAINTENANCE



BETTER COOLING





FEATURES	\$26 XC	
ENGINE 🐠		
Engine Type	3 Cylinder Diesel Engine	
HP Category	26	
No. of Cylinders	3	
Aspiration	Naturally	
Cubic Capacity (cc)	1319	
Rated RPM (+/-25mm)	2500	
Air Cleaner	Dry with Clogging Sensor	
Cold Start	Standard	
Max Torque (Nm)	76.3	
Exhaust	Silencer in the Engine Compartment, Downward Discharge	
TRANSMISSION 👭		
Drive	4 WD	
Clutch	Single Clutch	
Gearbox	6 Forward + 2 Reverse	
Front Axle	4WD	
Transmission	Sliding Mesh	
SPEED (FORWARD)		
Maximum Speed (Km/Hr)	16.2@2815 Fly Up	
Minimum Speed (Km/Hr)	1.64@2500 rated	
BRAKES 🊳		
Brakes	Oil Bath Brake	
Type of Actuation	Mechanical	
Parking Brake	Independent	
Differential Lock		
Differential Lock	Yes, Foot Operated	
PTO 🕪		
PTO (rpm)	540, 1000	
PTO (actuation)	Mechanical	
STEERING 🕒		
Steering	Power Steering	
ELECTRICAL		
Battery	12V, 65 Ah	
Alternator	12V, 42 A	
Seven Pin Trailer Socket	Standard	
HYDRAULICS O:-		
3 Point Linkage	Cat 1-N	
Stay Bars	Anchor Chain	
Additional Hydraulic Circuit	1 DA	
Hydraulic Lifting Capacity	750 Kg	
Lift Rods	Standard	
Litre per Minute (LPM)	13.5	

WWW	SOL	ISBFL	GIU	M.BE

FEATURES		\$26 XC			
SAFETY SWITCH					
PTO Safety		Standard			
Neutral Safety Switch	leutral Safety Switch		Standard		
Clutch Safety Switch		Standard			
CAPACITY (LTRS)(+/-5%	s) 🖪				
Fuel Tank (Lit)		28			
TURNING RADIUS	ř				
Without Brakes (m) as per Standard Tyres		3.18 (RHS), 3.10 (LHS)			
TYRE					
Front	6.0		6.00-12		
Rear		8.30-20			
DIMENSION & WEIGHT(+/-5%) 扇				
Weight (Kg)		1070, 1265 with Cabin	1070, 1265 with Cabin		
Wheel Base (mm)		1560			
Total Length (mm)		2760			
Total Width (mm)		1075 (max) - 1055 (min)	1075 (max) - 1055 (min)		
Height (mm) Up to ROPS		1955			
Min Ground Clearance (mm)		240			
Front Track (mm)		885			
Rear Track (mm)		835			
OTHERS \cdots					
Fuel Indicator Gauge		Standard			
Front Tow Hook		Standard	Standard		
Front & Rear Weights with std. Ballast		Front weights - 2 x 15 Kg			
Trailer Hitch		Drawbar / Optional Towbar			
ROPS		Yes			
OPTIONAL FEATURES	8 ►				
Cabin Option		Yes			
Tyres					
Radial Agri: Front Rear	Turf: Front Rear	Ind: Front Rear	GALAXY PRO		
6.5/80-12	23x8.50-12	23x8.50-12	FRONT 220/55R12		
280/70 R18	33x15.5-16.5	33x15.5-16.5	REAR 280/70R16		
Front Loader		YES optional			



